

5. FOR CONSTRUCTION DETAILS, REFER

1,12,14,15

17,18

12°X24

MD 175 EB

AERIAL CABLES	_____	A	_____
ELECTRICAL	_____	E	_____
TELEPHONE	_____	T	_____
GAS	_____	G	_____
SEWER	_____	S	_____
WATER	_____	W	_____
CABLE TV	_____	TV	_____
STORM DRAIN	_____	SD	_____

4 OF 5

1. THE CONDUIT TO BE INSTALLED ACROSS THE PROPOSED ROADWAY SHALL BE TRENCHED PRIOR TO PAVEMENT CONSTRUCTION.
2. DETECTORS SHALL BE INSTALLED PRIOR TO FINAL PAVEMENT SURFACE COURSE.
3. THE CONTRACTOR SHALL CONFIRM THE LOCATIONS OF THE PROPOSED GEOMETRICS PRIOR TO INSTALLATION OF SIGNAL EQUIPMENT.
4. ALL POLE AND CABINET FOUNDATIONS AND HANDHOLES SHALL BE INSTALLED AT FINAL GRADE.
5. FOR CONSTRUCTION DETAILS, REFER TO TS-1396E-CD.

R, OFFICE OF TRAFFIC

28 OF 46

THE WILSON T. BALLARD CO.
CONSULTING ENGINEERS
OWINGS MILLS, MARYLAND